



PVC绝缘护套叉形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

**Vinyl-Insulated Spade Terminal
(Apply in flexible wire)**

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin

SPADE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)						颜色 Color	只/包 Pcs/Pack
						W	L	F	E	Dφ	dφ		
SV 0.5-3	0.2-0.75 (24~18)	0.5	10A	#4	3.1	5.8	19.5	5.1	10.0	2.7	1.3	黄 yellow	1000
SV 0.5-4				#8	4.3	6.4	19.5	5.3					

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)						颜色 Color	只/包 Pcs/Pack
						W	L	F	E	Dφ	dφ		
SV 1.25-3	0.5~1.5 (22~16)	0.75	19A	#4	3.2	5.7	21.8	6.5	10.7	4.2	1.7	红 red	1000
SV 1.25-3.5S				#6	3.7	5.7	21.8	6.5					
SV 1.25-3.5L				#6	3.7	6.4	21.8	6.5					
SV 1.25-4S				#8	4.3	6.4	21.8	6.5					
SV 1.25-4M				#8	4.3	7.2	21.8	6.5					
SV 1.25-4L				#8	4.3	8.1	21.8	6.5					
SV 1.25-5S				#10	5.3	8.1	21.8	6.5					
SV 1.25-5L				#10	5.3	9.3	21.8	6.5					
SV 1.25-6S				1/4	6.4	9.5	21.8	6.5					
SV 1.25-6L				1/4	6.4	12.0	28.0	11.0					

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)						颜色 Color	只/包 Pcs/Pack
						W	L	F	E	Dφ	dφ		
SV 2-3	1.5~2.5 (16~14)	0.8	27A	#4	3.2	5.7	21.7	6.5	10.7	4.9	2.3	蓝 blue	1000
SV 2-3.5S				#6	3.7	5.7	21.7	6.5					
SV 2-3.5L				#6	3.7	6.2	21.7	6.5					
SV 2-4S				#8	4.3	6.4	21.7	6.5					
SV 2-4M				#8	4.3	7.2	21.7	6.5					
SV 2-4L				#8	4.3	8.1	21.7	6.5					
SV 2-5S				#10	5.3	8.1	21.7	6.5					
SV 2-5L				#10	5.3	9.5	21.7	6.5					
SV 2-6S				1/4	6.4	9.5	21.7	6.5					
SV 2-6L				1/4	6.4	12.0	27.7	11.0					