



**尼龙绝缘护套母插端子(适用于软线)**

- 材质: 黄铜
- 护套: 尼龙
- 温度: 105℃
- 表面处理: 镀锡

**Nylon-Insulated Female Terminal  
(Apply in flexible wire)**

- Terminal Body: Brass
- Insulation: Nylon
- Temperature: 105℃
- Plating: Tin

## FEMALE TERMINAL

型号 Item NO	导线截面mm <sup>2</sup> Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)					颜色 Color	只/包 Pcs/Pack				
					W	Dφ	dφ	L	H						
FDDN 1.25-110(5)	0.5~1.5 (22-16)	10A	0.5×2.8	0.3	3.2	4.1	1.7	19.8	11.0	红 red	1000				
FDDN 1.25-110(8)			0.8×2.8		3.2	4.1	1.7	19.8							
FDDN 1.25-187(5)			0.5×4.75	0.4	5.0	4.1	1.7	19.6							
FDDN 1.25-187(8)			0.8×4.75		5.0	4.1	1.7	19.6							
FDDN 1.25-205(5)					0.5×5.2		5.5	4.1				1.7	20.5		
FDDN 1.25-205(8)					0.8×5.2		5.5	4.1				1.7	20.5		
FDDN 1.25-250					0.8×6.35		6.6	4.1				1.7	20.5		

型号 Item NO	导线截面mm <sup>2</sup> Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)					颜色 Color	只/包 Pcs/Pack				
					W	Dφ	dφ	L	H						
FDDN 2-110(5)	1.5~2.5 (16-14)	15A	0.5×2.8	0.3	3.2	4.7	2.3	19.7	11.5	蓝 blue	1000				
FDDN 2-110(8)			0.8×2.8		3.2	4.7	2.3	19.7							
FDDN 2-187(5)			0.5×4.75	0.4	5.0	4.7	2.3	19.7							
FDDN 2-187(8)			0.8×4.75		5.0	4.7	2.3	19.7							
FDDN 2-205(5)					0.5×5.2		5.5	4.7				2.3	20.5		
FDDN 2-205(8)					0.8×5.2		5.5	4.7				2.3	20.5		
FDDN 2-250					0.8×6.35		6.6	4.7				2.3	20.8		

型号 Item NO	导线截面mm <sup>2</sup> Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)					颜色 Color	只/包 Pcs/Pack
					W	Dφ	dφ	L	H		
FDDN 5.5-250	4~6 (12-10)	24A	0.8×6.35	0.4	6.6	6.6	3.4	23.3	14.0	黄 yellow	1000