



PVC绝缘护套母插端子(适用于软线)

- 材质: 黄铜
- 护套: PVC
- 表面处理: 镀锡

**Vinyl-Insulated Female Terminal
(Apply in flexible wire)**

- Terminal Body: Brass
- Insulation: Vinyl
- Plating: Tin

FEMALE TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)					颜色 Color	只/包 Pcs/Pack
					W	Dφ	dφ	L	H		
FDD 1.25-110(5)	0.5~1.5 (22-16)	10A	0.5×2.8	0.3	3.2	3.8	1.7	19.8	10.6	红 red	1000
FDD 1.25-110(8)			0.8×2.8		3.2	3.8	1.7	19.8			
FDD 1.25-187(5)			0.5×4.75	0.4	5.0	3.8	1.7	19.5			
FDD 1.25-187(8)			0.8×4.75		5.0	3.8	1.7	19.5			
FDD 1.25-205(5)			0.5×5.2	5.5	3.8	1.7	20.0				
FDD 1.25-205(8)			0.8×5.2	5.5	3.8	1.7	20.0				
FDD 1.25-250			0.8×6.35	6.6	3.8	1.7	20.5				

型号 Item NO	导线截面mm ² Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)					颜色 Color	只/包 Pcs/Pack
					W	Dφ	dφ	L	H		
FDD 2-110(5)	1.5~2.5 (16-14)	15A	0.5×2.8	0.3	3.2	4.3	2.3	19.6	10.5	蓝 blue	1000
FDD 2-110(8)			0.8×2.8		3.2	4.3	2.3	19.6			
FDD 2-187(5)			0.5×4.75	0.4	5.0	4.3	2.3	19.5			
FDD 2-187(8)			0.8×4.75		5.0	4.3	2.3	19.5			
FDD 2-205(5)			0.5×5.2	5.5	4.3	2.3	19.4				
FDD 2-205(8)			0.8×5.2	5.5	4.3	2.3	19.4				
FDD 2-250			0.8×6.35	6.6	4.3	2.3	20.5				

型号 Item NO	导线截面mm ² Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)					颜色 Color	只/包 Pcs/Pack
					W	Dφ	dφ	L	H		
FDD 5.5-250	4~6 (12-10)	24A	0.8×6.35	0.4	6.6	5.4	3.4	23.0	13.4	黄 yellow	1000